

TAYLOR

Professional Quality Video Audio Microwave Links



S1770 100A

Frequency deviation ± 8 MHz
 Video bandwidth (-3 dB) 10Hz - 5MHz
 Input/output level 1Vpk-pk 75 Ω
 Differential Gain: $\pm 5\%$
 Differential Phase $\pm 5^\circ$
 Audio bandwidth typ 50Hz-17kHz
 Audio Input/output level 2x 0,7V 600 Ω rms Balanced XLR
 Frequency Selected approved bands 2.3GHz to 23GHz
 power output 20mW to 1W
 19" rack mounting 2U Transmitter 2U Receiver
 Voltage 110V and 220VAC
 CE compliant

Miniature transmitter



CCTV Video 2,4GHz

S1770 A

Standard configuration includes transmitter and receiver
 4 channel frequency:

Built in antenna, range 300m

S1770 B

Standard configuration includes transmitter and receiver
 4 channel frequency:

Frequency deviation ± 8 MHz
 Video bandwidth (-3 dB) 10Hz - 5MHz
 Input/output level 1Vpk-pk 75 Ω
 Differential Gain: - 18%
 Differential Phase $\pm 5^\circ$
 Audio bandwidth typ 1x 50Hz-15kHz
 Range with suitable antenna, 8km
 Housing protection
 Machined RF tight.
 IP54 splash-water protected
 Voltage 12VDC
 CE compliant

Police Security Mobile

S1770 D

1 channel: (Special police frequency).
 For police applications.

Housing protection
 IP54 splash-water protected

TCLP12-600 600mA 12VDC PSU



* Manufactured by Andrew



**2.45Ghz No licence
required .Plug
and play**



Two Audio Channels

**Custom made Radio and Video
Links up to 50 miles**

